

## IP ACCESS ROUTER



The all-round talent with UMTS ( 3G ) modem and 11n WiFi

### **bintec RS120wu**

- Integrated UMTS modem with HSxPA (7.2/5.76 Mbps)
- 5 x Gigabit Ethernet
- WLAN - 802.11n, 2.4/5 GHz
- Web-based configuration / wizards
- IPSec - 5 tunnels, HW acceleration
- IPv6
- Stateful Inspection Firewall



dual-stream n



## bintec RS120wu

### The all-round talent with UMTS ( 3G ) modem and 11n WiFi

The RS120wu HSDPA / UMTS GUI router is, thanks to its integrated HSUPA/HSDPA- (7.2/5.76 Mbps) UMTS ( 3G ) modem, particularly well-suited to mobile solutions and anywhere DSL is not available or high availability is required.

#### Product description

The bintec RS120wu is a HSDPA GUI router and, thanks to its comprehensive equipment, it is also a flexible 3G router. The integrated UMTS 3G modem with HSUPA, HSDPA, UMTS, EDGE, GPRS and GSM support can be used as a primary internet connection or as a backup gateway.

This HSDPA business gateway comes in the fan-free metal housing, which guarantees long-term reliability in critical corporate applications and is ideal to be used as a 3G business router in SMEs, branch offices and home offices.

In addition to the integrated UMTS ( 3G ) modem, the RS120wu HSDPA enterprise gateway also has five gigabit Ethernet ports, which can be configured for LAN, WAN or DMZ. The bintec RS120wu HSDPA enterprise router also comes with a SFP slot for optical fibre expansion modules, e.g. for connecting to an optical fibre broadband connection. Thanks to the variety of different connection technologies used, the bintec RS120wu 3G / HSDPA branch office router sets new standards for the flexibility of access routers. By using an external indoor or outdoor UMTS ( 3G ) antenna, it is possible to significantly improve reception. This is a huge advantage as in many branch offices connectivity often decreases due to building structure.

The bintec RS120wu 3G / HSDPA GUI gateway is supplied ex works with a licence for five hardware-accelerated IPSec tunnels.

The bintec RS120wu 3G / HSDPA GUI router also has a dual band WiFi module with 2.4 and 5 GHz, which supports IEEE 802.11n. The new 802.11n technology permits gross transmission speeds of up to 300 Mbps and offers a better range than the previous 802.11g technology. However, due to the integrated IEEE 802.11n compatibility mode, this means that the bintec RS120wu wireless router is compatible with all IEEE 802.11g and IEEE 802.11abgh clients and supports the mixed operation of IEEE 802.11n clients and IEEE 802.11b/g or IEEE 802.11a/h clients. This enables the seamless exchange of existing wireless routers through the bintec RS120wu router without significant changes to the infrastructure. Clients that already support 802.11n benefit automatically from the higher data throughput.



#### Using functions flexibly

Only a few functions are required to forward data packets between two networks. The bintec RS120wu 3G / HSDPA GUI gateway with its web based interface has features that go far beyond

just routing and allow it to be integrated into complex IT infrastructures. By using Extended Routing and NAT (ERN) the data can be routed in IP routing according to criteria such as IP protocols (Layer 4), source or destination IP address, source or destination port, TOS/DSCP, source or destination interface and the status of the destination interface. In addition, you can also use network address translation to translate the data traffic for both inbound and outbound connections and individually for each interface based on a wide range of criteria. The comprehensive multicast support makes this 3G / HSDPA GUI gateway ideal for use in multimedia and streaming applications.

The Stateful Inspection Firewall (SIF) of this professional router offers effective protection against attacks from the Internet through dynamic packet filtering. Firewall handling is made easier through numerous pre-configured services. An optional content filter rounds off the security functions of the RS120wu advanced graphical user interface gateway\*. In this case, all the outgoing Internet enquiries are classified and allow contents not wanted to be reliably filtered out.

The basic equipment of the RS Series advanced graphical user interface routers also offers a SIP application level gateway (ALG) for the direct connection of IP telephones in the network or for registering with a VoIP provider, without affecting the security of the WAN connection. The corresponding releases in NAT and the internal Stateful Inspection Firewall are controlled automatically by ALG for the length of the communication.

Quality of Service is more than a watchword in bintec 3G / HSDPA wizard routers. Thanks to the rising convergence between voice and data, the classification of data streams is gaining in importance. Our 3G / HSDPA wizard gateways provide corresponding QoS mechanisms for prioritising the VoIP traffic ahead of normal internet traffic, for example and to guarantee it sufficient bandwidth. Alternatively you can give normal data traffic priority over e-mail traffic. The bintec QoS implementation of the 3G / HSDPA gateway allows voice data to be processed before e-mail data, for example, within a VPN tunnel.

The DNS proxy function supports the LAN for address implementation and the automated IP configuration of PCs is carried out over an integrated DHCP server.

### **Comprehensive IPSec implementation**

The IPSec implementation integrated in our advanced graphical user interface gateways works not only with preshared keys but also with certificates. This allows a public key infrastructure to be created for maximum security. (The German Federal Office for Information Security also recommends the use of certificates.)

Furthermore, the IPSec implementation of the bintec 3G / HSDPA GUI router offers support when creating VPN connections with dynamic IP addresses: Even small branch offices can be reached without having to be permanently online. If both VPN nodes only have dynamic IP addresses, confidential information can continue. The exchange of IP addresses is carried out over a dynamic DNS provider. The configuration of the comprehensive IPSec implementation can be done over a wizard based interface or over a web interface.

### **Load Balancing/Backup**

The 3G / HSDPA business gateway offers a unique level of flexibility thanks to the wide variety of interfaces supported. The bintec RS 120wu 3G / HSDPA gui gateway supports the ability to configure two interfaces as WAN interfaces. As a result, there is not only more bandwidth available, but there is the opportunity to spread data traffic across individual WAN connections according to load or data type. Equally, you can use a UMTS ( 3G ) connection for the VPN connection to the head office and use a second WAN port for a low-cost ADSL connection to guarantee the company's other data traffic. If either connection fails, the other can take over the entire data transfer.

### **Simple configuration and maintenance via web based interface**

The RS120wu router is configured over an advanced graphical user interface (GUI). The GUI is a

web-based user interface surface that you can use from any PC with an up-to-date Web browser connection via HTTP or encrypted HTTPS. All standard functions can be configured easily via the wizard interface which is integrated into the RS120wu router's advanced web interface. . Indeed, an assistant configuration provides some predefined wireless network terms which guarantees an easy and fast configuration of this HSDPA GUI gateway. The RS120wu HSDPA GUI router also offers the opportunity to manage the devices locally and remotely over other configuration accesses such as Telnet, SSH and GSM dialin. DIME Manager from Teldat is a free tool for managing Teldat devices. This Dime Manager is aimed at administrators who manage networks with up to 50 devices. The software simplifies the management and configuration of Teldat routers or access points either individually or in logical groups.

When Teldat developed the DIME Manager, simple and efficient operation was the primary aim. It allows, for example, software updates or configurations to be applied to individual devices or groups of devices simply by drag and drop. DIME Manager recognises and manages new devices in the network using SNMP multicasts, in other words independent of their current IP address.

\* Content filtering is a fee-paying service and is available as a 30-day trial version.

## Variants

<b>bintec RS120wu - UK</b> (5510000257)	IP Access Router; incl. UMTS modem; .11n WLAN; incl. IPSec (5 tunnels), certificates, HW encryption; 4+1 Gigabit Eth. switch; USB port; SFP module slot; UK version.
<b>bintec RS120wu</b> (5510000220)	IP Access Router; incl. UMTS modem; .11n WLAN; incl. IPSec (5 tunnels), certificates, HW encryption; 4+1 Gigabit Eth. switch; USB port; SFP module slot; german and intern. version.

## Features

Wireless LAN	
WLAN Mode	Access Point
WLAN Mode	WLAN client mode; Transparent client for direct connection of Ethernet devices
WLAN standards	802.11n (Mimo 2x3); 802.11b; 802.11g; 802.11a; 802.11h
Frequency bands 2.4 GHz indoor/outdoor (EU)	2.4 GHz Indoor/Outdoor (2412-2472 MHz) max. 100 mW EIRP (Germany). The permitted transmission power may vary in other countries.
Frequency bands 5 GHz indoor (EU)	5 GHz indoor (5150-5350 MHz) max. 200 mW EIRP allowed (Germany). The permitted transmission power may vary in other countries.
Frequency bands 5 GHz outdoor (EU)	5 GHz outdoor (5470-5725 MHz) max. 200 mW EIRP allowed (Germany). The permitted transmission power may vary in other countries.
WLAN modes	2.4 GHz operation: 802.11b only; 802.11g only, 802.11b/g/n mixed; 802.11b/g/n mixed long; 802.11b/g/b mixed short; 802.11b/g/n; 802.11g/n; 802.11n only; 5 GHz Operation: 802.11a only; 802.11a/n; 802.11n only
Automatic Rate Selection (ARS)	Available
Transmission rate	Automatic fallback or fixed transmission rate selectable



## Wireless LAN

Data rates for 802.11a,h (5 GHz)	54, 48, 36, 24, 18, 12, 9 and 6 Mbps (OFDM modulation)
Data rates for 802.11n (2.4 / 5 GHz)	MSC0-15 enables physical rates up to 150 Mbps at 20 MHz channels bandwidth, 2 streams, short guard interval; MSC0-15 enables physical data rates up to 300 Mbps at 40 MHz channels bandwidth, 2 streams, short guard interval
Roaming (access point mode)	Seamless roaming with IAPP (artem Inter Access Point Protocol)
Number of spatial streams (802.11n)	1 or 2
Broadcast SSID	On/off switchable
Broadcast SSID	Data prioritization for TOS data, 802.11e/WMM
WMM 802.11e Power Save	Support of active WLAN clients, which support 802.11e power save
Country-specific settings	Channel settings according regulatory domain (802.11d) permitted.
WDS	Wireless Distribution System: Include high security TKIP and AES, interoperable with W1002n, Wlx40, Wlx65n, RS120wu, RS232aw, RS232bw and RS232jw
TPC	TPC (transmission power control): For 5 GHz, automatic reduction of transmission power according EN301893
Data rates for 802.11b,g (2.4 GHz)	11, 5.5, 2 und 1 Mbps (DSSS modulation); 54, 48, 36, 24, 18, 12, 9 and 6 Mbps (OFDM modulation)
Fast roaming 802.1x (access point mode)	Pre authentication and PMK caching allows fast roaming by 802.1x encryption
Power Managment for Clients	Registering of up to 250 clients simultaneously in access point mode.
Buffer pool	For cushioning of peaks
Bandwidth (802.11n)	20/40 MHz (bundling of two adjoining 20 MHz channels to one 40 MHz channel)
Short guard interval (802.11n)	On/off switchable; increase of throughput by reduction of the guard intervals from 800ns to 400ns
RTS/CTS	RTS/CTS threshold adjustable
DTIM Period	Adjustable
VLAN	Network segments on layer2 possible. Per SSID one VLAN ID available. Static VLAN configuration according IEEE 802.1q; up to 32 VLANs supported.
Multi SSID	Depending on the complexity of configuration up to 8 service sets per radio module, with virtual access points and own MAC address per SSID.
Inter Cell Repeating	Inter traffic blocking for public hot spot (PHS) applications for preventing of communication radio client to radio client in a single radio cell.

## WLAN Electric Characteristics

Receiver Sensitivity @ 2.4 GHz 802.11b/g	1 Mbps -91 dBm; 2 Mbps -90 dBm; 5.5 Mbps -89 dBm; 11 Mbps -88 dBm; 6 Mbps -90 dBm; 9 Mbps -89 dBm; 12 Mbps -88 dBm; 18 Mbps -86 dBm; 24 Mbps -83 dBm; 36 Mbps -80 dBm; 48 Mbps -76 dBm; 54 Mbps -74 dBm
Receiver Sensitivity @ 2.4 GHz 802.11n 20 MHz	MSC0 -89 dBm; MSC1 -87 dBm; MCS2 -85 dBm; MCS3 -82 dBm; MCS4 -79 dBm; MSC5 -75 dBm; MCS6 -73 dBm; MCS7 -70 dBm; MCS8 -83 dBm; MCS9 -84 dBm; MCS10 -81 dBm; MCS11 -79 dBm; MCS12 -80 dBm; MCS13 -72 dBm; MCS14 -68 dBm; MCS15 -67 dBm

## WLAN Electric Characteristics

Receiver Sensitivity @ 2.4 GHz 802.11n 40 MHz	MSC0 -87 dBm; MSC1 -84 dBm; MCS2 -82 dBm; MCS3 -79 dBm; MCS4 -75 dBm; MSC5 -71 dBm; MCS6 -69 dBm; MCS7 -67 dBm; MCS8 -86 dBm; MCS9 -83 dBm; MCS10 -79 dBm; MCS11 -77 dBm; MCS12 -74 dBm; MCS13 -69 dBm; MCS14 -67 dBm; MCS15 -65 dBm
Receiver Sensitivity @ 5 GHz 802.11n 20 MHz	MSC0 -88 dBm; MSC1 -85 dBm; MCS2 -83 dBm; MCS3 -81 dBm; MCS4 -78 dBm; MSC5 -74 dBm; MCS6 -72 dBm; MCS7 -70 dBm; MCS8 -88 dBm; MCS9 -85 dBm; MCS10 -83 dBm; MCS11 -80 dBm; MCS12 -77 dBm; MCS13 -72 dBm; MCS14 -70 dBm; MCS15 -68 dBm
Receiver Sensitivity @ 5 GHz 802.11a/h	6 Mbps -88 dBm; 9 Mbps -87 dBm; 12 Mbps -86 dBm; 18 Mbps -84 dBm; 24 Mbps -82 dBm; 36 Mbps -78 dBm; 48 Mbps -74 dBm; 54 Mbps -73 dBm
Output power (without antenna gain)	Adjustable in following steps: 5, 8,11,14,16 und 17.5 dBm. Maximal power varies depending on data rate and frequency band.
Tx Power @ 2.4 GHz 802.11b/g	1 Mbps 16 dBm; 2 Mbps 16 dBm; 5.5 Mbps 16 dBm; 11 Mbps 16 dBm; 6 Mbps 17,5 dBm; 9 Mbps 17,5 dBm; 12 Mbps 17 dBm; 18 Mbps 17 dBm; 24 Mbps 15 dBm; 36 Mbps 15 dBm; 48 Mbps 13 dBm; 54 Mbps 13 dBm
Tx Power @ 2.4 GHz 802.11n 20 MHz/40 MHz	MSC0 17.5 dBm; MSC1 17,5 dBm; MCS2 17 dBm; MCS3 17 dBm; MCS4 15 dBm; MSC5 15 dBm; MCS6 13 dBm; MCS7 13 dBm; MCS8 17.5 dBm; MCS9 17.5 dBm; MCS10 17 dBm; MCS11 17 dBm; MCS12 15 dBm; MCS13 15 dBm; MCS14 13 dBm; MCS15 13 dBm
Tx Power @ 5 GHz 802.11b/g	1 Mbps 16 dBm; 2 Mbps 16 dBm; 5.5 Mbps 16 dBm; 11 Mbps 16 dBm; 6 Mbps 17.5 dBm; 9 Mbps 17.5 dBm; 12 Mbps 17 dBm; 18 Mbps 17 dBm; 24 Mbps 15 dBm; 36 Mbps 15 dBm; 48 Mbps 13 dBm; 54 Mbps 13 dBm
Tx Power @ 5 GHz 802.11n 20 MHz/40 MHz	MSC0 17.5 dBm; MSC1 17.5 dBm; MCS2 17 dBm; MCS3 17 dBm; MCS4 15 dBm; MSC5 15 dBm; MCS6 13 dBm; MCS7 13 dBm; MCS8 17.5 dBm; MCS9 17.5 dBm; MCS10 17 dBm; MCS11 17 dBm; MCS12 15 dBm; MCS13 15 dBm; MCS14 13 dBm; MCS15 13 dBm

## GSM / UMTS

Supported standards	Support of UMTS (3G), HSxPA (3G+; HSDPA with up to 7.2 Mbps, HSUPA with up to 5.76 Mbps), GPRS, Edge and GSM
UMTS (3G) / WCDMS bands	900/1900/2100 MHz
GSM/GPRS/EDGE bands	850/900/1800/1900 MHz
Diversity	Receive diversity on AUX antenna for 900/1900/2100 MHz
Maximum transmission power	+24 dBm

## VPN

PPTP (PAC/PNS)	Point to Point Tunneling Protocol for establishing fo Virtual Privat Networks, inclusive strong encryption methods with 128 Bit (MPPE) up to 168 Bit (DES/3DES, Blowfish)
GRE v.0	Generic Routing Encapsulation V.0 according RFC 2784 for common encapsulation
L2TP	Layer 2 tunnelling protocol inclusive PPP user authentication
Number of VPN tunnels	Inclusive 5 active VPN tunnels with the protocols IPSec, PPTP, L2TP and GRE v.0 (also in combination possible)
IPSec	Internet Protocol Security establishing of VPN connections
Number of IPSec tunnels	Inclusive 5 active IPSec tunnels

VPN	
IPSec Algorithms	DES (64 Bit), 3DES (192 Bit), AES (128,192,256 Bit), CAST (128 Bit), Blowfish (128-448 Bit), Twofish (256 Bit); MD-5, SHA-1, RipeMD160, Tiger192 Hashes
IPSec hardware acceleration	Integrated hardware acceleration for IPSec encryption algorithms DES, 3DES, AES
IPSec IKE	IPSec key exchange via preshared keys or certificates
IPSec IKE Config Mode	IKE Config Mode server enables dynamic assignment of IP addresses from the address pool of the company. IKE Config Mode client enables the router, to get assigned dynamically an IP address.
IPSec IKE XAUTH (Client/Server)	Internet Key Exchange protocol Extended Authenticaion client for login to XAUTH server and XAUTH server for logging of XAUTH clients
IPSec IKE XAUTH (Client/Server)	Inclusive the forwarding to a RADIUS-OTP (One Time Password) server (supported OTP solutions see <a href="http://www.teldat.de">www.teldat.de</a> ).
IPSec NAT-T	Support of NAT-Traversal (Nat-T) for the application at VPN lines with NAT
IPSec IPComp	IPSec IPComp data compression for higher data throughput via LZS
IPSec certificates (PKI)	Support of X.509 multi-level certificates compatible to Microsoft and Open SSL CA server; upload of PKCS#7/8/10/12 files via TFTP, HTTP, LDAP, file upload and manual via FCI
IPSec SCEP	Certificates management via SCEP (Simple Certificate Enrollment Protocol)
IPSec Certificate Revocation Lists (CRL)	Support of remote CRLs on a server via LDAP or local CRLs
IPSec Dead Peer Detection (DPD)	Continuous control of IPSec connection
IPSec dynamic DNS	Enables the registering of dynamic IP addresses by a dynamic DNS provider for establishing a IPSec connection.
IPSec RADIUS	Authentication of IPSec connections at a RADIUS server. Additionally the IPSec peers, which were configured on a RADIUS server, can be loaded into the gateway (RADIUS dialout).
IPSec Multi User	Enables the Dial-in of several IPSec clients via a single IPSec peer configuration entry
IPSec QoS	The possibility to operate Quality of Service (traffic shaping) inside of an IPSec tunnel
IPSec NAT	By activating of NAT on an IPSec connection it is possible, to implement several remote locations with identical local IP address networks in different IP nets for the VPN connection
IPSec throughput (1400)	34 Mbps with 1400 Byte packets with AES 256 / AES 128 / 3 DES encryption
IPSec throughput (256)	11 Mbps with 256 Byte packets with AES 256 / AES 128 / 3 DES encryption

Security	
Encryption WEP/WPA	WEP64 (40 Bit key), WEP128 (104 Bit key), WPA Personal, WPA Enterprise, WPA2 Personal, WPA2 Enterprise
Inter Cell Repeating	Inter traffic blocking for public hot spot (PHS) applications for preventing of communication radio client to radio client in a single radio cell.
IEEE802.11i Authentisierung und Verschlüsselung	802.1x/EAP-MD5, 802.1x/EAP-TLS, 802.1x/EAP-TTLS, 802.1x/EAP-PEAP, key management, PSK/TKIP encryption, AES encryption, 802.1x/EAP
Access Control List (ACL)	MAC address filter for WLAN clients

## Security

VLAN	Network segmentation on layer 2 possible, one VLAN ID per SSID. Static VLAN configuration according to IEEE 802.1q; supports up to 32 VLANs.
NAT/PAT	Symmetric Network and Port Address Translation (NAT/PAT) with randomly generated ports inclusive Multi NAT (1:1 translation of whole networks)
Policy based NAT/PAT	Network and Port Address Translation via different criteria like IP protocols, source/destination IP Address, source/destination port
Policy based NAT/PAT	For incoming and outgoing connections and for each interface variable configurable
Content Filtering	Optional ISS/Cobion Content filter (30 day test license inclusive)
Stateful Inspection Firewall	Packet filtering depending on the direction with controlling and interpretation of each single connection status
Packet Filter	Filtering of IP packets according to different criteria like IP protocols, source/destination IP address, source/destination port, TOS/DSCP, layer 2 priority for each interface variable configurable

## Routing

Policy based Routing	Extended routing (Policy Based Routing) depending of diffent criteria like IP protocols (Layer4), source/destination IP address, source/destination port, TOS/DSCP, source/destination interface and destination interface status
Multicast IGMP	Support of Internet Group Management Protocol (IGMP v1, v2, v3) for the simultaneous distribution of IP packets to several stations
Multicast IGMP Proxy	For easy forwarding of multicast packets via dedicated interfaces
Multicast inside IPsec tunnel	Enables the transmission of multicast packets via an IPsec tunnel
RIP	Support of RIPv1 and RIPv2, separated configurable for each interface
Extended RIP	Triggerd RIP updates according RFC 2091 and 2453, Poisoned Rerverse for a better distribution of the routes; furthermore the possibility to define RIP filters for each interface.
Routing throughput (1518)	199 Mbps with 1518 Byte packets
Routing throughput (256)	198 Mbps with 256 Byte packets

## Protocols / Encapsulations

PPP/MLPPP	Support of Point to Point Protocol (PPP) for establishing of standard PPP connections, inclusive the Multilink extension MLPPP for the bundeling of several connections
PPPoE (Server/Client)	Point-to-Point Protocol over Ethernet (Client and Server) for establisching of PPP connections via Ethernet/DSL (RFC 2516)
MLPPPoE (Server/Client)	Multilink extension MLPPPoE for bundeling several PPPoE connections (only if both sides support MLPPPoE)
DNS	DNS client, DNS server, DNS relay and DNS proxy
DYN DNS	Enables the registering of dynamic assigned IP addresses at adynamic DNS provider, e.g. for establishing of VPN connections
DNS Forwarding	Enables the forwarding of DNS requests of free configurable domains to assigned DNS server.



## Protocols / Encapsulations

DHCP	DHCP Client, Server, Proxy and Relay for simplified TCP/IP configuration
Packet size controlling	Adaption of PMTU or automatic packet size controlling via fragmentation

## Quality of Service (QoS)

Policy based Traffic Shapping	Dynamic bandwidth management via IP traffic shaping
Bandwidth reservation	Dynamic reservation of bandwidth, allocation of guaranteed and maximum bandwidths
DiffServ	Priority Queuing of packets on the basis of the DiffServ/TOS field
Layer2/3 tagging	Conversion of 802.1p layer 2 prioritisation information to layer 3 diffserv attributes
TCP Download Rate Control	For reservation of bandwidth for VoIP connections

## Redundancy / Loadbalancing

BRRP	Optional: Bintec Router Redundancy Protocol for backup of several passive or active devices with free selectable priority
BoD	Bandwidth on Demand: dynamic bandwidth to suit data traffic load
Load Balancing	Static and dynamic load balancing to several WAN connections on IP layer
VPN backup	Simple VPN backup via different media. Additional enables the Teldat interface based VPN concept the application of routing protocols for VPN connections.

## Layer 2 Functionality

Bridging	Support of layer 2 bridging with the possibility of separation of network segment via the configuration of bridge groups
VLAN	Support of up to 32 VLAN (Virtual LAN) for segmentation of the network in independent virtual segments (workgroups)
Proxy ARP	Enables the router to answer ARP requests for hosts, which are accessible via the router. That enables the remote clients to use an IP address from the local net.

## Logging / Monitoring / Reporting

Internal system logging	Syslog storage in RAM, display via web-based configuration user interface (http/https), filter for subsystem, level, message
External system logging	Syslog, several syslog server with different syslog level configurable
E-Mail alert	Automatic E-Mail alert by definable events
SNMP traps	SNMP traps (v1, v2, v3) configurable
Activity Monitor	Sending of information to a PC on which Brickware is installed

## Logging / Monitoring / Reporting

IPSec monitoring	Display of IPSec tunnel and IPSec statistic; output via web-based configuration user interface (http/https)
Interfaces monitoring	Statistic information of all physical and logical interfaces (ETH0, ETH1, SSIDx, ...), output via web-based configuration user interface (http/https)
WLAN monitoring	Detailed display for radio, VSS, WDS links, bridge links, client links.
WLAN Monitoring	Display for each link: MAC address, IP address, TX packets, RX packets, signal strength for all receiver antennas, signal-to-noise ratio, data rate; output via web-based configuration user interface (http/https)
IP accounting	Detailed IP accounting, source, destination, port, interface and packet/bytes counter, transmission also via syslog protocol to syslog server
RADIUS accounting	RADIUS accounting for PPP, PPTP, PPPoE and ISDN dialup connections
Keep Alive Monitoring	Control of hosts/connections via ICMP polling
Tracing	Detailed traces can be done for different protocols e.g. ISDN, PPPoE, ... generation local on the device and remote via DIME Manager
Tracing	Traces can be stored in PCAP format, so that import to different open source trace tools (e.g. Wireshark) is possible.

## Administration / Management

RADIUS	Central check of access authorization at one or several RADIUS server, RADIUS (PPP, IPSec inclusive X-Auth and login authentication)
RADIUS dialout	On a RADIUS server configured PPP und IPSec connection can be loaded into the gateway (RADIUS dialout).
TACACS+	Support of TACACS+ server for login authentication and for shell command authorization
Time synchronization	The device system time can be obtained via ISDN and from a SNTP server (up to 3 time server configurable). The obtained time can also be transmitted per SNTP to SNTP clients.
Automatic Time Settings	Time zone profiles are configurable. That enables an automatic change from summer to winter time.
Supported management systems	DIME Manager, XAdmin
Configurable scheduler	Configuring of time and event controlled tasks, e.g. reboot device, activate/deactivate interface, activate/deactivate WLAN, trigger SW update and configuration backup
Configuration Interface (FCI)	Integrated web server for web-based configuration via HTTP or HTTPS (supporting self created certificates). This user interface is by most of Teldat GmbH products identical.
Software update	Software updates are free of charge; update via local files, HTTP, TFTP or via direct access to the Teldat web server
Remote maintenance	Remote maintenance via telnet, SSL, SSH, HTTP, HTTPS and SNMP (V1,V2,V3)
Configuration via serial interface	Serial configuration interface is available
GSM remote maintenance	Remote maintenance via GSM login (V110/V120)

## Administration / Management

Device discovery function	Device discovery via SNMP multicast.
On The Fly configuration	No reboot after reconfiguration required
SNMP	SNMP (v1, v2, v3), USM model, VACM views, SNMP traps (v1, v2, v3) configurable, SNMP IP access list configurable
SNMP configuration	Complete management with MIB-II, MIB 802.11, Enterprise MIB
Configuration export and import	Load and save configurations, optional encrypted; optional automatic control via scheduler
SSH login	Supports SSH V1.5 and SSH V2.0 for secure connections of terminal applications
HP OpenView	Integration into Network Node Manager
XAdmin	Support of XAdmin roll out and configuration management tool for larger router installations (IP+GSM)

## Interfaces

Ethernet	5 x 10/100/1000 Mbps Ethernet Twisted Pair, autosensing, Auto MDI/MDI-X, up to 4 ports can be switches as additional WAN ports incl. load balancing, all Ethernet ports can be configured as LAN or WAN.
SFP slot	SFP slot for conventional optical 10/100/1000 Mbps Ethernet SFP module
WLAN	IEEE 802.11a/b/g/n; 1 radio module, 2.4 und 5 GHz band, 3 external antennas
USB 2.0 host	USB 2.0 full speed host port for connecting LTE(4G) or UMTS(3G) USB sticks (supported sticks: see <a href="http://www.teldat.org">www.teldat.org</a> )
Serial console	Serial console interface / COM port (mini USB)
GSM/UMTS (3G)	UMTS (3G), HSxPA (3G+), GPRS, Edge or GSM with integrated GSM/UMTS (3G) modem
External UMTS antenna connectors	Two SMA antenna connectors for external UMTS antennas
External WLAN antenna connectors	Three reverse SMA antenna connectors for external WLAN antennas

## Hardware

Realtime clock	System time persists even at power failure for some hours.
Wall mounting	Integrated in housing
Environment	Temperature range: Operational 0°C to 40°C; storage -10°C to 70°C; Max. rel. humidity 10 - 95% (non condensing)
Power supply	External wall power supply 110-240V / 12 V DC, 1.5 A, with energy efficient switching controller; complies with EuP directive 2008/28/EC
Power consumption	Less than 5 Watt
Housing	Metal case, opening for Kensington lock, connectors at back side, prepared for wall mounting
Dimension	Ca. 235 mm x 31.5 mm x 146,5 mm (W x H x D)
Weight	Ca. 1100g

## Hardware

Fan	Fanless design therefor high MTBF
Reset button	Restart or reset to factory state possible
Status LEDs	Power, Status, 10 * Ethernet, SFP, WLAN, UMTS (3G), USB
Certification	Wi-Fi Certified according 802.11abgn (Rel.7.9.4)
Standards and certifications	R&TTE Directive 1999/5/EG; EN 55022; EN 55024 + EN 55024/A1; EN61000-3-2; EN 61000-3-3; EN 61000-4-4; EN 60950-1; EN 300 328; EN 301 489-17; EN 301 489-1; EN 301 893; EN 301 489-7; EN 301 489-24; EN 301 908-1; EN 301 908-2; EN 301 511

## Content of Delivery

Manual	Quick Installation Guide in German and English
DVD	DVD with system software, management software and documentation
Ethernet cable	1 Ethernet cable, 3m
Power supply	Wall power supply 110-240V / 12 V DC, 1.5 A, with high efficient switching controller
WLAN antenna	Three external 3 dBi dipol dualband antennas
UMTS (3G) antenna	Two external 2 dBi dipol quadband antennas

## Service

Warranty	2 year manufacturer warranty inclusive advanced replacement
Software Update	Free-of-charge software updates for system software (BOSS) and management software (DIME Manager)

## Accessoires

### Software Licenses

<b>RS-Series-BRRP</b> (5500001023)	RS-Series software license for Bintec Router Redundancy Protocol (BRRP)
<b>Cobion Content Filter Small</b> (80551)	Cobion content filter for RSxxx, Rxx02, RTxx02 series; R230a(w), R232b(w), TR200, R1200(w/wu), R3000(w), R3400, R3800, R232aw; list price for one year

### Pick-up Service / Warranty Extension

<b>Service Package 'medium'</b> (5500000812)	Warranty extension of 3 years to a total of 5 years, including advanced replacement for Teldat products of the category 'medium'. Please find a detailed description as well as an overview of the categories on <a href="http://www.teldat.de/servicepackages">www.teldat.de/servicepackages</a> .
--	---

### Product Services

<b>HotSpotHosting 1yr 1 location</b> (5510000198)	HotSpot solution hosting fee for 1 year and 1 location
---	--

## Product Services

<b>HotSpotHosting 2yr 1 location</b> (5500000861)	HotSpot solution hosting fee for 2 year and 1 location
<b>Additional HotSpot location</b> (5510000199)	Additional location for the HotSpot solution (551000198, 5500000861) valid for one year

## Add-ons

<b>Home Compenser</b> (5500000852)	novero Home Compenser®; GSM/GPRS/EDGE/UMTS/HSCSD/HSDPA/HSUPA send and receive signal booster, inclusive antenna and 7m cable, SMA connector for RS120wu, RS230au+, RS232bu+
<b>Active Antenna UMTS-SMA</b> (5500001336)	Active UMTS (3G) antenna by novero for direct connection to a router, SMA connector for RS120wu, RS230au+, RS232bu+, UMTS band 1, 7db, 15m cable
<b>Active Antenna UMTS-USB-sticks</b> (5500001017)	novero active UMTS (3G) antenna for UMTS (3G) USB modems, UMTS band 1 active antenna, 7db, 15m cable
<b>PS-EURO-RSxxx</b> (5500000729)	Power supply EURO for RSxxx
<b>ANT-4G-LTE-Cross-Pol</b> (5500001467)	Cross polarised 8 dBi Mimo multi-band LTE(4G)-UMTS(3G) antenna incl. Mounting kit and 5 m cable for outdoor usage, SMA connector for RS232j-4G, RS120wu, RS230au+, RS232bu+
<b>ANT-Omni-3G-UMTS</b> (5500000853)	Omni-directional multi-band GSM-3G (UMTS) antenna incl. mounting kit and 5 m cable for outdoor usage, SMA connector for RS120wu, RS230au+, RS232bu+

## Cables

<b>Console Cable MiniUSB to DSUB9</b> (5500000717)	Serial console cable for RS, RT, Rxx02 Series and hybrid (Mini USB to D-SUB 9)
--	--